

## Technical data



## SPLIT MURAL MKG



DC Inverter fan



Optional 3-way valve



2 tubes



Condensate pump



Remote control



LED Display



Auto swing function



Easy installation and maintenance

### MODEL

			HTW-MKG-V300B	HTW-MKG-V400B	HTW-MKG-V600B
Power Supply		V,P,HZ	220-240V (1 Phase ~ 50Hz)		
<b>PERFORMANCE</b>					
Cooling <sup>1</sup>	Capacity (H/M/L)	<b>kW</b>	2,91/2,54/2,19	3,81/3,3/2,88	4,87/4,26/3,79
	Water flow rate (H/M/L)	<b>m<sup>3</sup>/h</b>	0,51/0,45/0,38	0,67/0,57/0,51	0,85/0,72/0,65
Heating <sup>2</sup>	Capacity (H/M/L)	<b>kW</b>	3,23/2,77/2,42	4,3/3,65/3,09	5,26/4,68/3,96
	Water flow rate (H/M/L)	<b>m<sup>3</sup>/h</b>	0,56/0,49/0,42	0,73/0,64/0,56	0,89/0,80/0,68
Heating <sup>3</sup>	Capacity (H/M/L)	<b>kW</b>	3,76/3,22/2,77	5,08/4,33/3,77	6,31/5,57/4,77
<b>FEATURES</b>					
Sound pressure level (H/M/L)		<b>dB(A)</b>	32/27/23	45/39/35	44/40/35
Air flow (H/M/L)		<b>m<sup>3</sup>/h</b>	585/485/413	825/689/590	979/849/717
Coil	Row		2	2	2
	Max. working pressure	<b>Mpa</b>	1,6	1,6	1,6
	Diameter	<b>mm</b>	Φ7	Φ7	Φ7
<b>DIMENSIONS AND WEIGHT</b>					
Net dimensions (WxHxD)		<b>mm</b>	915x290x230	915x290x230	1072x315x230
Net weight		<b>Kg</b>	12,7	12,7	14,9
<b>CONNECTIONS</b>					
Pipe connection	Water inlet/outlet pipe	<b>inch</b>	RC3/4	RC3/4	RC3/4
	Drain pipe	<b>mm</b>	ODΦ20	ODΦ20	ODΦ20

### Notes:

Based on Eurovent conditions:

H: High fan speed; M: Medium fan speed; L: Low fan speed.

1: Cooling mode (2 and 4-pipe coil): entering air temperature 27°C dB/19°C WB, entering/leaving water temperature 7°C/12°C, high fan speed.

2: Heating mode (1) (2-pipe coil): entering air temperature 20°C dB, entering/leaving water temperature 45/50°C, high fan speed.